



150MT™

HEAVY DUTY STARTER





FEATURES & BENEFITS

- **Optimized pinion speed** provides best-in-class cranking performance
- **High performance power pack** provides optimized performance for better engine starts and supports multiple improved vehicle power sources/battery loading
- Long life operation and **over crank thermal protection** offers more reliability to meet new vehicle requirements
- **Improved mechanical rigidity** to support new vehicle operating requirements
- **Warranty:** 4 year/unlimited miles (Applicable to U.S. and Canada only)


SPECIFICATIONS

Engine Size	12V up to 16 Liters, 24V up to 18 Liters
Rotation	Clockwise (viewing pinion end)
Mounting	SAE 1, SAE 3 and customer specific as requires
Pinion Data	11 Tooth, 6-8 Pitch; 12 Tooth, 8-10 Pitch; 12 Tooth Mod 3-metric
Output	12V peak at 7.3kW, 24V peak at 9.0kW
Weight	14.4kg/31.75 lbs
Diameter	115 mm/4.53 inches
Heavy Duty Drive	Electrical Soft-Start Engagement System Overrunning Clutch
Starting Torque with Gear Ratio	4.3:1

SUPERIOR STARTS – PREMIUM ENDURANCE



150MT HEAVY DUTY STARTER



ENGINE	VOLTAGE	39MT	150MT	COMPETITIVE CROSS REFERENCES
Detroit Diesel Series 60 (S60), CAT C9, C10, C11, C12, C13 & C15, Cummins ISM, M11, N14 & ISX 15, MaxxForce 15, Mack E7	12V	8200308	61014400	PC1479, IN1478, FL0975, FL0777, FL0579, MIB970777, MIB970975, D616005003, D616002004
DD 13/15/16 2016 and newer	12V	61008898	61015900	FLA579, M110613, M110R2613SE
Cummins ISC & ISL, MaxxForce 9, 10, 11 & 13, Paccar PX-8 & PX-9, International DT466, DT530, DT570 & HT570	12V	8200433	61017311	PC1379, PC2679, PC72679, IN1378, IN3179, M110610, M110606, M105302, M105602, 428000-2690, 228000-5311
CAT C12, C13, C15, Cummins ISM, ISX, N14, Detroit S60, Mack E7	24V	8200330	61015901	PV2479, PC83579, MC2378



® For Customer Service or
Technical Assistance call 800-372-0222

08 | 2025
DELCOREMY.COM